

AHCH01-5202  
In-truck Charger



In-truck charger for firefighting series

- Working Temperature Range: 0°C to 50°C (32°F to 122°F)

## ▪ Specification

| General                    |   |
|----------------------------|---|
| Power Input                | 12 -24V DC in to Cigarette lighter adapter , 5V or 12V DC, 2A max. from cigarette lighter adapter.<br>12 -24V DC in to DC-DC converter, 12V DC, 2A max. from DC-DC converter.                                       |
| Battery Charging Indicator | Solid red: battery is charging.<br>Solid green: battery is fully charged.   |
| Charging Base Indicator    | Solid red: Charging base is abnormal.<br>Solid green: Charging base is powered on.  |
| Battery Charging Time      | 5V cigarette lighter adapter: 9.5 hours for battery, 4 hours for camera.<br>12V cigarette lighter adapter: 3 hours for battery, 4 hours for camera.<br>DC to DC converter: 3 hours for battery, 4 hours for camera. |
| Working Temperature Range  | 0°C to 50°C (32°F to 122°F)   |
| EMC                        | EN 301 489-1, EN 301 489-17, EN IEC 61000-6-2, EN IEC 61000-6-3, EN 61326-1   |
| Weight                     | Approx. 680g (1.50 lb)  |
| Packaging Accessories      | USB 2.0 A to USB Type-C cable, 5V Cigarette lighter adapter, DC to DC converter, Fuse, Screws and rivets kit, Quick Start Guide   |
| Dimension                  | 257.4 mm × 143.3 mm × 125.1 mm (10.1" × 5.6" × 4.9")  |

## ▪ Available Model

AHCH01-5202

## ▪ Dimension



