TC19
Thermal Sight



HIKMICRO HIKTac TC19 Thermal Sight is equipped with a 256×192 @12 μm (NETD<18 mK) thermal detector. Its 3.1-inch large AMOLED display offers an immersive viewing and tracking experience with better situational awareness.

· Key Feature

- NETD<18 mK Thermal Sensitivity
- 3.1-inch AMOLED Display
- 260 g Lightweight
- Killflash Lens Protector

· Specification


Thermal Module	
Image Sensor	VOx Uncooled Focal Plane Arrays
Max. Resolution	256×192
Frame Rate	50 Hz
Pixel Interval	12 μm
Response Waveband	8 μm to 14 μm
NETD	Less than 18 mK (@25°C, F# = 1.0)
Lens (Focal Length)	19 mm, F1.0
Focus Mode	Focus Ring
Detection Range	900 m
Magnification	1.2× to 9.6×
Min. Focusing Distance	1 m
Field of View(H×V), Degrees/m @100 m	9.2°×6.9°
Image Display	
Display	3.1-inch AMOLED Display, 600×450
Palettes	Black Hot, White Hot, Red Hot, Iron Bow
Tone Adjustment	Cold, Warm
Brightness Adjustment	Yes
Contrast Adjustment	Yes
Zoom Pro	Yes
HSIS (HIKMICRO Shutterless Image System)	Yes
Image Pro 3.0	Yes
Sync Pro	Yes
System	
Record Video	Yes
Capture Snapshot	Yes
Standby Mode	Yes
Storage	Built-in EMMC (4 GB)
PIP	Yes
Hotspot	Yes
Local Album	Yes
Zeroing Profiles	5
Freeze Zeroing	Yes
Power Supply	
Battery Type	One replaceable and rechargeable 18650 battery
Battery Operating Time	4h
Type-C Power Supply	DC 5V/2A, USB Type-C interface

General	
Protection Level	IP67
Dimension	106.9 mm×94.8 mm×86.7 mm
Weight	260 g (without battery)
Working Temperature	-30°C to 45°C

· Available Model

HM-TR02-19S2G/W-TC19

· Dimension



Unit: mm[inch]

COMPLIANCE NOTICE: The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.

HIKMICRO



HIKMICRO SIGHT

Download on the App Store

GET IT ON Google Play

BATTERY 1 YEAR

FULL PRODUCT 3 YEARS

DETECTOR 10 YEARS

Hikmicro Hunting.Global | HIKMICRO Outdoor | www.hikmicrotech.com | hikmicro hunting.global | HIKMICRO | info@hikmicrotech.com

Room 313, Unit B, Building 2, 399 Danfeng Road, Xixing Subdistrict, Binjiang District, Hangzhou, Zhejiang

© Hangzhou Microimage Software Co., Ltd. All rights reserved. | Data subject to change without notice!