

# A50E

## Digital Day & Night Vision Scope



HIKMICRO ALPEX 4K A50E Digital Day & Night Vision Scope can perform in all ambient light that is present. It has an advanced 3840 × 2160 FHD detector, 50 mm lens, and 1920 × 1080 0.49" sub-round OLED display, providing full-color clarity in daytime and classic black & white viewing at night. The traditional-style 30 mm tube design meets the needs of professional hunters who value traditions and seek technological superiority. The scope is suitable for both field and forest hunting.

### Key Feature

- 3840 × 2160 resolution CMOS detector
- 50 mm lens with F1.2 to 2.5 adjustable aperture
- 1920 × 1080 resolution 0.49-inch sub-round OLED display
- Supports Day/Night mode
- Supports recoil-activation recording with audio, built-in EMMC (64 GB)
- Up to 11 hours of continuous operation
- Replaceable and rechargeable battery

# Specification


Main	
Max. Resolution	3840 × 2160
Frame Rate	50 Hz
Lens (Focal Length)	50 mm, F1.2 to 2.5 Adjustable Aperture
Detection Range	Day: 1000 m
Min. Focusing Distance	10 m
Magnification	3.5x to 28.0x (8x) Support Continuous Zooming
Field of View	8.8° × 5.0°/15.3 m × 8.6 m @100 m
Image Display	
Display	1920 × 1080, 0.49 inch, OLED
Image Mode	Day, Night
Exit Pupil	6 mm
Eye Relief	55 mm
Diopter (Range)	-5 D to 5 D
System	
Record Video	On-board Video Recording
Record Video Resolution	1920 × 1080
Capture Snapshot	Yes
Audio Recording	Yes
Recoil-activation Recording	Yes
Standby Mode	Yes
Storage	Built-in EMMC (64 GB)
PIP	Yes
Freeze Zeroing	Yes
Distance Measurement	NA
Zeroing Profiles	5
Max. Recoil	1000 g/0.4 ms
Hotspot	Yes
Ballistic Calculation	NA
Power Supply	
Battery Type	Two Rechargeable Lithium Batteries (Internal), One Replaceable and Rechargeable 18650 Battery (External)
Battery Operating Time	11 hours of Continuous Running (@25°C, Hotspot off)
Power Supply	5 VDC/2 A, USB Type-C Interface
General	
Mounting	Standard 30 mm
Protection Level	IP67

Working Temperature	-30°C to 55°C (-22°F to 131°F)
Dimension	439.8 mm × 71.4 mm × 84.0 mm
Weight	1080 g without External Battery
<b>Laser Rangefinder</b>	
Safety Class for Laser	NA
Wavelength	NA
Max. Measuring Range	NA
Measurement Accuracy	NA
Min. Measuring Range	NA


## ▪ Available Model

HM-TR3F-50S2/WV-A50E

## ▪ Dimension



## ▪ Accessories





HIKMICRO SIGHT



HIKMICRO Outdoor hikmicro\_outdoor HIKMICRO Outdoor HIKMICRO info@hikmicrotech.com <http://hikmicrotech.com/en>

Room 313, Unit B, Building 2, 399 Danfeng Road, Xixing Subdistrict, Binjiang District, Hangzhou, Zhejiang  
@hangzhou microimage software co.,Ltd .2020 | data subject to change without notice!