HIKMICRO

SX75LR 4.0

Thermal Image Scope



Key Feature

- 1280 × 1024 Thermal Detector, 75 mm F1.2 Lens
- High sensitivity thermal module NETD < 12 mK
- LRF-inside Design, 1200 m Measuring Range
- 6000J High Shock Resistance
- 8 mm Exit Pupil & 55 mm Eye Relief

Specification


Thermal Module	
Image Sensor	VOx Uncooled Focal Plane Arrays
Max. Resolution	1280 × 1024
Frame Rate	50 Hz
Pixel Interval	12 μm
Response Waveband	8 μm to 14 μm
NETD	Less than 12 mK
Lens (Focal Length)	75 mm, F1.2
Focus Mode	Side Focus Ring
Detection Range	3600 m
Min. Focusing Distance	10 m
Magnification	3.0×-30.0×
Field of View(H × V), Degrees / m @100m	12.1° × 9.7°/21.2 m × 17 m
Image Display	
Display	2560 × 2560, 1.03 inch AMOLED
Palettes	Black Hot, White Hot, Red Hot, Fusion, Red Monochrome, Green Monochrome
Exit Pupil	8 mm
Eye Relief	55 mm
Diopter (Range)	-5D to 5D
Brightness Adjustment	Yes
Tone Adjustment	Cold, Warm
Contrast Adjustment	Yes
HSIS (HIKMICRO Shutterless Image System)	Yes
Image Pro 4.0	Yes
Intelligent Zoom	Yes
Sync Pro	Yes
System	
Record Video	On-board Video Recording
Capture Snapshot	Yes
Audio Recording	Yes
Recoil-activation Recording	Yes
Storage	Built-in EMMC (64 GB)
PIP	Yes
Hotspot	Yes
Distance Measurement	Yes
Zeroing Profiles	5
Max. Recoil	6000J

Freeze Zeroing	Yes
Standby Mode	Yes
Ballistic Calculation	Yes
Local Album	Yes
Power Supply	
Battery Type	Two rechargeable Lithium batteries (internal), one replaceable and rechargeable 18650 battery (external)
Battery Operating Time	7-hour continuous running (25°C, LRF on)
Type-C Power Supply	5 V DC/2 A, USB Type-C interface, Supports QC3.0 * Only the built-in battery will be charged via the type-C cable. Use the battery charger to charge the external battery.
General	
Mounting	Rail Mounting
Dimension	445.7mm × 93.5mm × 78.7mm
Weight	1140 g with external battery
Working Temperature	-30°C to 55°C (-22 °F to 131°F)
Protection Level	IP67
Center Height	41mm
Laser Rangefinder	
LRF-inside Design	Yes
Wavelength	905 nm
Safety Class for Laser	Class 1
Max. Measuring Range	1200 m
Measurement Accuracy	±1 m
Min. Measuring Range	10 m

· Available Model


HM-TR8C-75Y3G/WLR-SX75LR 4.0

· Dimension



Unit: mm

· Accessories



COMPLIANCE NOTICE: The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries

HIKMICRO



HIKMICRO SIGHT

Download on the App Store

GET IT ON Google Play

BATTERY 1 YEAR

FULL PRODUCT 3 YEARS

DETECTOR 10 YEARS

Hikmicro Hunting.Global | HIKMICRO Outdoor | www.hikmicrotech.com | hikmicro hunting.global | HIKMICRO | info@hikmicrotech.com

Room 313, Unit B, Building 2, 399 Danfeng Road, Xixing Subdistrict, Binjiang District, Hangzhou, Zhejiang

© Hangzhou Microimage Software Co., Ltd. All rights reserved. | Data subject to change without notice!