



Thermal Image Binocular
Habrok 4k Series (**V5.5.154 build 260624**)

Release Notes

TABLE OF CONTENTS

Chapter 1 Introduction.....	0
Chapter 2 Functional Optimization	2
2.1 Newly added Ballistic Calculation function	2
2.2 Newly added Zoom Extended Ratio mode	2
2.3 Configurable Optical Palettes	2
2.4 LRF Box Customization	2
2.5 Captured image includes GPS information.....	2
2.6 Bugs Fixed	2

Chapter 1 Introduction

This document introduces new features and optimizations in V5.5.154 build 260624 firmware version of the products.

Version Information

Item	Description
Firmware Version	V5.5.154 build 260624
Models	Habrok 4k: HE25L(N) 5.5-22x60; HQ35L 5.5-22x60
Mobile Client	HIKMICRO Sight V2.11.1 build260610 and above

Chapter 2 Functional Optimization

2.1 Newly added Ballistic Calculation function

- You can use this feature in combination with a scope without a ballistic calculator to help you better calculate the bullet drop point, with units of MOA, MRAD/MIL, CM, INCH, 1/4 MOA Click, 1/3 MOA Click, 0.1 MIL Click, 0.05 MIL Click.
- BC value refresh mechanism: No refresh during pitch changes, only refreshes with LRF trigger. However, the calculation of the BC value still takes the pitch angle into account.

2.2 Newly added Zoom Extended Ratio mode

- New zoom options for dual channels, inserting intermediate magnifications between large zoom steps.

2.3 Configurable Optical Palettes

- Support enable/disable Black&White/Yellow/Green optical night vision modes in Custom Palettes menu.

2.4 LRF Box Customization

- Adjustable 3 style and 4 color.

2.5 Captured image includes GPS information.

- This update is for the subsequent functional layout of the hunt ECOSYSTEM.

2.6 Bugs Fixed

- Resolved white spots, frame drops, and GPS display issues.



 Hikmicro Hunting.Global

 Hikmicro Hunting.Global

 HIKMICRO Outdoor

 HIKMICRO

 www.hikmicrotech.com

 support@hikmicrotech.com